

MIG



ROBUSTESSE - ROBUST
FIABLE - BETROUWBAAR



www.cerdi.be



cerdi
BELGIUM

MIG










MIG



		AUTOBOX 253 AUTOBOX 253 AK	AUTOBOX 303 AUTOBOX 303 AK	SAMMY 350	SAMMY 420	SAMMY 500	SAMMY 600	MIGGY 200	MPI 303	SPI 403	TPI 403
Alimentation / Netspanning	V	3 * 230 / 400	3 * 230 / 400	3 * 230 / 400	3 * 230 / 400	3 * 230 / 400	3 * 230 / 400	1 * 230	3 * 400	3 * 400	3 * 400
Fusibles / Zekering	A	25/16	35/20	35/20	50/32	63/40	80/60	20	16	16	16
Puissance / Vermogen	kVA	8	12	14	18	22	25	5.6	9.6	15	15
Réglage / Instelbereik	A	30-260	50-310	50-360	60-440	70-560	80-650	5-200	5-300	5-400	5-400
Tension à vide / Nulllastspanning	V	16,5-29,5	14-35	15-40	18-40	21-55	24-60	72	78	78	78
Positions de réglage / Regelposities		10	30	30	30	28	28	continu	continu	continu	continu
Facteur de marche / Inschakelduur	%	60	60	60	60	60	60	60	60	60	60
Rendement / Rendement		0.88	0.88	0.88	0.88	0.88	0.88	0.89	0.89	0.89	0.89
Isolation / IP.. / Isolatie / IP..		F / IP23	F / IP23	F / IP21	F / IP21	F / IP21	F / IP21	F / IP21	F / IP23	F / IP23	F / IP23
Technologie / Technologie		transfo	transfo	transfo	transfo	transfo	transfo	IGBT	IGBT	IGBT	IGBT
Ø fils / draad	mm	0,6/1,0	0,6/1,2	0,8-1,6	0,8-2,4	0,8-2,4	0,8-3,2	0,6-0,8	0,6-1,2	0,6-1,6	0,6-1,6
Type de bobine / bobijn type	kg/2	< 18kg	< 18kg	< 18kg / O	< 18kg / O	< 18kg / O	< 18kg / O	< 18kg	< 18kg	< 18kg	< 18kg
Galets moteur / Draadgeleiding	/2	2 * 4 / O	2 * 4 / O	4	4	4	4	2 - 4 / O	4	4	4
Puissance moteur / Vermogen motor	W /3	90	90	140 / 150 / O	140 / 150 / O	140 / 150 / O	140 / 150 / O	90	90	90	90
Dévidoir / Uitvoering	/4	compact / Da4m (AK)	compact / Da4m (AK)	DA4 / O	DA4 / O	DA4 / O	DA4 / O	compact	compact	compact	compact
2t/4t / 2t/4t	/5	+	+	O	O	O	O	+	+	+	S
Refroidisseur eau / Waterkoeler	/6	-	-	O / CU1	O / CU1	O / CU1	O / CU1	-	O / CU6	O / CU6	O / CU6
Poids / Gewicht	kg	104 / 112	110/118	190	215	255	265	20	40	40	40
Dimensions / Afmetingen	mm	895*450*770 (AK+435)	895*450*770 (AK+435)	970*450*820	970*450*820	970*450*905	970*450*905	580*310*425	895*320*770	895*320*770	895*320*770

N°

DESCRIPTION - BESCHRIJVING

100.200.253 100.200.303		AUTOBOX 253 AUTOBOX 303
100.210.253 100.210.303		AUTOBOX 253AK AUTOBOX 303AK
100.211.350 100.211.420 100.211.500 100.211.600		SAMMY 350 SAMMY 420 SAMMY 500 SAMMY 600
100.202.200		MIGGY 200
100.202.303 100.205.403 100.206.403		MPi 303 SPi 403 TPi 403
100.300.005 100.300.010		Da2m 90 W (2 galets - 2 wielen Autobox AK) Da4m 90 W (4 galets - 4 wielen Autobox AK)
100.300.000 100.300.200		Da4 140 W (4 galets - 4 wielen SAMMY) Da4 150 W (4 galets - 4 wielen SAMMY)
145.100.001		CERDI Cu1 (15l) Refroidisseur eau - Watertank 230V
145.100.006		CERDI Cu6 (10l) Refroidisseur eau - Watertank 230/400V
110.210.003		2 / 4 takt
110.210.004		V/A mètre - Volt - en ampèremeter (set)
110.210.010		Sécurité eau - flow switch
720.350.000		Câble int. air - Tussenkabel luchtgekoeld (ppm)
720.500.000		Câble int. air - Tussenkabel luchtgekoeld < 300A (ppm)
720.350.500		Câble int. eau - Tussenkabel watergekoeld < 450 A (ppm)
720.500.500		Câble int. eau - Tussenkabel watergekoeld < 600A (ppm)
735.000.000		Housse (air) - Mantelovertrek luchtgekoeld (ppm)
735.000.500		Housse (eau) - mantelovertrek watergekoeld (ppm)
110.620.500		Chariot / Kar MIGGY200

**cerdi**
BELGIUMwww.cerdi.be

DEALER